

SuperScrape Impressions

→ LOGO MAT • INDOOR & OUTDOOR



→ WHY CHOOSE THIS MAT?

SuperScrape Impressions mats feature your custom logo or artwork overlaid onto a SuperScrape mat. Multi-colour images are created by molding a digitally printed polymeric material into the durable nitrile rubber surface of the mat.

- **High Definition Photographic quality** images are printed on thermoplastic material and molded into rubber
- Textured **slip resistant** surface effectively removes dirt and soil
- Rubber that is resistant to chemical, greases and oil
- **80 standard colour options**
- Rubber anti-slip backing with 34% post-industrial recycled content in the rubber polymer

→ SPECIFICATIONS

Material	• 100% Nitrile Rubber with 34% post-industrial recycled content in the polymer – phthalate free – For maximum oil resistance, durability, and performance. Compression –molded with reinforced borders on all four sides.
Other properties	• Thickness: 3.5 mm • Total weight: 4,3 kg/m² • Durometer: 65 • Tensil: 1600
Colour	80 standard colours
Recommended use	Recommended for use in commercial and industrial settings where branding or messaging is required/preferred along with the debris removal qualities of a scraper mat. Excellent for customization with a company logo, slogan, or safety and quality reminders.

→ STANDARD SIZES

60x40 (max. logo size: 50x30)




75x85 (max. logo size: 55x65)

85x150 (max. logo size: 65x130)

115x180 (max. logo size: 95x160)

150x250 (max. logo size: 110x230)

Size Tolerance: +/- 5%



→ CLEANING INSTRUCTIONS

SuperScrape Impressions mats can be commercially laundered (see laundering instructions) or cleaned using the instructions below:


1. Scrub with a deck brush (when needed) using detergent with a neutral PH
2. Rinse with a hose or pressure washer
3. Lay flat or hang to dry

→ LAUNDERING INSTRUCTIONS

SuperScrape Impressions mats can be commercially laundered periodically to remove soil. The formula below does not require extensive mechanical action or drying.

1. Flush 2-3 minutes, medium water level, cold water
2. Break 5-10 minutes, high water level, 49 °C
3. Rinse 2 minutes, high water level, cold water
4. Rinse 2 minutes, high water level, cold water
5. Drain 2 minutes
6. Lay mats flat following removal from washer. Allow to cool before rolling.

→ COLOURS

								
S1	S2	S3	S4	S5	S6	S7	S8	S9
								
S10	S11	S12	S13	S14	S15	S16	S17	S18
								
S19	S20	S21	S22	S23	S24	S25	S26	S27
								
S28	S29	S30	S31	S32	S33	S34	S35	S36
								
S37	S38	S39	S40	S41	S42	S43	S44	S45
								
S46	S47	S48	S49	S50	S51	S52	S53	S54
								
S55	S56	S57	S58	S59	S60	S61	S62	S63
								
S64	S65	S66	S67	S68	S69	S70	S71	S72
								
S73	S74	S75	S76	S77	S78	S79	S80	